

Cargotrailer CP300-LH PRO with plastic cover

(SC0167TIB15)

It is a new trailer that is registered and ready to take part in traffic immediately after the purchase.

We initiate the change of ownership in the e-environment of the Transport Administration no later than the next working day. The actions of the change of ownership must be confirmed by the Buyer within 5 calendar days.

PRO series trailers are particularly suitable for professional use. The trailer on the reinforced all-welded frame is designed for everyday use when transporting particularly heavy loads. In addition, the trailers of PRO series are equipped with an innovative front hatch. There is a PPF (Paint Protection Film) in the corners of the front hatch, which increases the protection of the surfaces most damaged by stones flying from under the car's wheels.

The trailer is made of hot-dip galvanized sheet metal, suitable for northern conditions. Strong 2-groove side profiles increase trailer rigidity. Waterproof hubs ensure a longer life for the bearings. Metal step-resistant fenders and step boards enable more comfortable use of the trailer. The cargo box is equipped with strap loops on the inside and hooks on the outside to secure the load. Strap loops are attached to the side posts of the trailer to ensure greater tensile strength when securing the load. In addition, the bottom of the trailer can be fully utilized in this way, and the fastening loops do not interfere with loading and unloading (e.g. bulk material). The tilting cargo box and fully welded frame tailgate allows the trailer to be used for loading and unloading lighter vehicles (lawn tractor, ATV, etc.).

Check out the [PRO trailer product video](#)



Tehnilised andmed

Kasti laius (m):	1.5
Kasti pikkus (m):	3
Raam:	Welded
Täismass (kg):	750
Tühimass (kg):	294
Kandevõime (kg):	456
Poordikõrgus (m):	0.40
Haagise pikkus (m):	4.41
Haagise laius (m):	1.88
Sild:	lehtvedru
Pidurid:	EI
Rehvid:	155R13C M+S
Rattapoltide arv:	5
Laadimiskõrgus (m):	0.54

Standardvarustus

- ✓ Täiskeervisraam
- ✓ Tugevdatud kinnitusega tugiratas
- ✓ Ülitugev keevisliitega sild (sillatala tehniline kandevõime 2000 kg, rummud koormustaluvusega 2 x 1000kg)
- ✓ Lamineeritud veekindel põhjavineer
- ✓ Veokasti kallutus
- ✓ Eemaldatav esi- ja tagaluuk
- ✓ Vineeriga tugevdatud tagaluuk
- ✓ Täiskeervisraamil luugid
- ✓ Tugevdatud tagapaneel
- ✓ Metallist pealeastumist taluvad poritiivad
- ✓ Tugevdatud C rehvid
- ✓ Astmelauad
- ✓ Veopea 1500kg

✓ Plastkaas
WWW.TIKI.EE



- ✓ Fermiga tugevdatud veotiisel
- ✓ Rataste kinnitus 5 poldiga
- ✓ 8 kinnitusaasa (sees) ja 4 kinnituskonksu (väljas)
- ✓ LED ääretuled
- ✓ Pistik 13 klemmi