BX600-L boat trailer with roller rails

(EC0600TI)

TIKI's new generation boat trailer combines innovative design and practicality, offering a safe and convenient transport solution for various boat types. It is designed with even the most demanding user in mind. The BX series has been developed in collaboration with boat manufacturers and users. The hot-dip galvanized welded frame single-axle trailer is designed for everyday use as well as for those who need a trailer only once or twice a year.

NB! When choosing a trailer, keep in mind the dimensions and weight of your boat, including engine, fuel and accessories.

The frame with extended side beams increases stability and safety when driving. Leaf suspension with shock absorbers relieves the effect of impact holes on the trailer and improves driving performance. The adjustable length drawbar allows the trailer to be adjusted according to the length of the boat and the centre of gravity. On the winch tower, it is possible to adjust the height of the winch and the nose support, as well as the angle relative to the ground. A winch with a brake ensures comfortable and safe operation. For safer and more convenient movement of the boat without a towing vehicle, the support wheel is supported from two points. Waterproof hubs ensure a longer life for the bearings. The trailer frame is equipped with large strong mounting loops to securely fasten the boat. The tilting mechanism helps to direct the boat onto the trailer. Metal step-on fenders and step boards provide better access to the boat on the trailer. The taillights are attached to the mudguard of the trailer. Thanks to this, the trailer can be operated without moving the lights.

Upgrade your trailer with accessories for the best user experience.



Tehnilised andmed

Max paadi pikkus (m): 4.5

Raam: Welded Täismass (kg): 600

Tühimass (kg): Kandevõime (kg):

Haagise pikkus (m): 4.55 Haagise laius (m): 1.6 Sild: leaf spring

Pidurid: NO

Rehvid: 155 R13 84N 4 x 100 M+S

Standardvarustus

- Tugevdatud kinnitusega tugiratas
- Tugev kuumtsingitud keevisraam
- Vastupidav keevisliitega sild 3-leheliste vedrudega
- Reguleeritava pikkusega tiisel
- 2 kiilurulli
- Reguleeritav vintsipukk koos vintsi ja ninatoega
- Piduriga vints
- ✓ Kallutusmehhanism 2 kiilurulliga
- Rullsiinid
- Veekindlad rummud
- Tugevad kinnitusaasad
- Metallist pealeastumist taluvad poritiivad
- Astmelauad
- Tasakaalustatud rattad M+S rehvidega
- Veekindlad LED ääretuled
- Pistik 13 klemmi

