

# Cargo trailer CP300-LH PRO BLACK DUPLEX

(SC0167TICS)

Black Duplex is the first serial production trailer featuring a Duplex surface protection system (hot-dip galvanizing + paint). It offers C5 corrosion protection class and is significantly more durable than Magnelis® or standard HDG coating. In addition to its practicality, the trailer has a stylish appearance and is as easy to wash as a car.

The front hatch of the Black Duplex is made of a strong metal frame with a durable polymer coating. This solution provides enhanced protection for areas most affected by stones thrown up by vehicle wheels.

With double surface coating and a reinforced full-welded frame, this trailer is designed for daily use with especially heavy loads. It is manufactured using hot-dip galvanized and painted sheet metal suitable for Nordic conditions, sourced from [SSAB](#) – the world's largest and most environmentally friendly manufacturer of special and premium steels. Strong dual-groove side profiles increase the trailer's rigidity. Leaf spring suspension with shock absorbers reduces the impact of potholes and improves driving performance. Waterproof hubs ensure a longer life for the bearings. The metal mudguards and step boards, coated with a special durable paint, withstand stepping and improve ease of use. The paint also provides effective protection against slipping and stone chips.

The cargo box is equipped with strap loops on the inside and hooks on the outside to secure the load. Strap loops are attached to the side posts of the trailer to ensure greater tensile strength when securing the load. In addition, the bottom of the trailer can be fully utilized in this way, and the fastening loops do not interfere with loading and unloading (e.g. bulk material). The cargo bed is galvanized and painted both inside and out, ensuring excellent corrosion resistance and easier maintenance. The tilting cargo box and fully welded frame tailgate allows the trailer to be used for loading and unloading lighter vehicles (lawn tractor, ATV, etc.).

## Tehnilised andmed



Kasti laius (m):	1.5
Kasti pikkus (m):	3
Raam:	Welded
Täismass (kg):	750
Tühimass (kg):	294
Kandevõime (kg):	456
Poordikõrgus (m):	0.40
Haagise pikkus (m):	4.41
Haagise laius (m):	1.88
Sild:	leaf spring
Pidurid:	NO
Rehvid:	155R13C M+S
Rattapoltide arv:	5

## Standardvarustus

- ✓ Täiskeevisraam
- ✓ Nii seest kui ka väljast Duplex pinnakaitsesüsteemiga kaetud haagis
- ✓ Tugevdatud kinnitusega tugiratas
- ✓ Ülitugev keevisliitega sild (sillatala tehniline kandevõime 2000 kg, rummud koormustaluvusega 2 x 1000kg)
- ✓ Lamineeritud veekindel põhjavineer 12mm
- ✓ Veokasti kallutus
- ✓ Eemaldatav komposiit esiluuk
- ✓ Eemaldatav esi- ja tagaluuk
- ✓ Vineeriga tugevdatud tagaluuk
- ✓ Täiskeevisraamil luugid
- ✓ Tugevdatud tagapaneel
- ✓ Metallist pealeastumist taluvad poritiivid
- ✓ Spetsiaalväraviga kaetud metallist poritiivid ja astmelauad

[WWW.TIKI.EE](http://WWW.TIKI.EE)



- ✓ Tugevdatud C rehvid
- ✓ Astmelauad
- ✓ Veopea 1500kg
- ✓ Plastkaas
- ✓ Fermiga tugevdatud veetiisel
- ✓ Rataste kinnitus 5 poldiga
- ✓ 8 kinnitusaasa (sees) ja 2 + 2 kinnituskonksu (väljas)
- ✓ LED ääretuled
- ✓ Pistik 13 klemmi